

<u>METHOD</u>	<u>TEST</u>	<u>MIN</u>	<u>MAX</u>	<u>Result</u>	<u>Units</u>
ASTM D664A	Total Acid Number		0.5	<0.05	mg KOH/g
Visual	Visual Appearance at 25°C	Clear & Bright		Clear & Bright	-
ASTM D482	Ash Content		0.01	<0.010	wt%
ASTM D4737A	Cetane Index	48		54.3	-
ASTM D4530	Micro Carbon Residue on 10% Bottom		0.20	<0.10	wt%
ASTM D1500	ASTM Color		2.0	L0.5	-
ASTM D130	Copper Corrosion at 50°C for 3 hrs		1	1a	-
ASTM D4052	Density @ 15 °C		890.0	849.5	kg/m ³
ASTM D86	Distillation Range	-	-	-	-
ASTM D86	95% Recovered		370	368.9	°C
ASTM D93A	Flash Point	55		77.0	°C
ASTM D7371	Biodiesel Content	Nil		Nil	vol%
ASTM D445	Kinematic Viscosity @ 40 °C	2.0	4.5	4.424	mm ² /s
ASTM D6079	Lubricity		520	450	µm
ASTM D97	Pour Point		Report	+3	°C
ASTM D5453	Sulfur		500	460	mg/kg
ASTM D2709	Water and Sediment		0.05	<0.01	vol%